

Product datasheet



VK Easy Rack PDU, Switched,
1U, 1 Phase, 2.5kW, 250V, 10A,
8x C13 Locking outlets, IEC60320
C14 inlet

VK-ZPDU-8C13-10AA21

Overview

This VK Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.

Lead Time Usually in Stock

Main

Colour	Black
Pdu Type	Switched
Cord Length	Optional
Circuit breaker	1P 10A

Complementary

Input Voltage	200V-250V
Input Plug Type	IEC 60320 C14
Output Voltage	200V-250V
Outlet Type And Quantity	8 IEC 60320 C13 Locking
Input Current Limits	10A
Load Capacity	2500 VA
Network Frequency	50/60 Hz
Rack Units	1U
Mounting Position	Horizontal
Height	44mm
Depth	210mm
Width	440mm
Net Weight	3.1KG

Environment

Product Certifications	CE
Ambient Air Temperature For Operation	-5...45 °C
Relative Humidity	5...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage Altitude	0.00...15240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	130mm
Package 1 Width	310mm
Package 1 Length	520mm
Package 1 Weight	3.8KG

Contractual warranty

Warranty	2 year repair or replace
----------	--------------------------